Model 5AG-5 by **HIGH CAPACITY**



Wash Sheet Pans Horizontally with the optional Pan Rack



Double Duty Model designed to multiply your dishwashing capability. Features 20 1/2" door opening, air-gap fill, dual screening. Washes 74 racks per hour with two powerful 1 1/2 HP Pumps.



At American Dish Service, Quality People, Designs, and Products have been the foundations of our organization for over 45 years.

www.americandish.com



Model 5AG-5

TAKES CARE OF BIG JOBS IN NO TIME FLAT

- Cleans 74 racks per hour
- Water consumption is 1.6 gallons per rack
- Great Door Clearance at 20 1/2"
- Top Mount Controls with Auto Start
- Stainless Steel air gap

Effective: 4/05

- Quick release spray arms
- Two Quick service 1 1/2 HP pumps
- Door safety switch external prime switches
- Delime Switch located in the control panel





-3/4" FPT Water Inlet 21.0" (53.3 cm) SECTION A-A SECTION B-B TOP VIEW TYPICAL TABLE DETAILS CAUTION: 124.5 cm TOP VIEW SIDE VIEW FRONT VIEW "Manafacturer reserves the right to modify these specifications in compliance with regulatory agencies and manufacturing agencies."

		American Dish	Service
		Manufacturers of Ware Washing	Equipment
Model	5AG-	S	

	FAMILY MODELS		
	5AGS	58	5AHS
RATED CAPACITY (racks/hour)	74	56	46
WASH TIME (in seconds)	45	60	75
RINSE TIME (in seconds)	30	45	60
DWELL (in seconds)	15	15	15
TOTAL CYCLE TIME (in seconds)	90	120	150

WATER TEMPERATURE 120 Deg. F/49 Deg. C MINIMUM WATER CONSUMPTION (NSF) 3.2 GALS. PER CYCLE(12.1 Liters) MOTOR (2) 1.5 H.P. 1.125 KW **ELECTRICAL RATING (NEC)** 115 VOLTS Single Phase

Connect to two Supply Sources Using 8-6 AWG Copper Wire. Circuit Protection: 20 AMP Circuit Breaker or Fuse with a 20 Amp Rating Breaker or Fuse with a 20 Amp Rating
OR
Connect to Supply Sources Using 8-6 AWG
Copper Wire suitable for at least 75 Deg. C(167 Deg. F.)
Circuit Protection: 40 AMP Circuit

RACK SIZE (2) DOOR CLEARENCE WATER INLET DRAIN SIZE (Scrap Trap) **HEIGHT (Doors Open)** HEIGHT (Doors Closed) WIDTH (Overall) WIDTH (Table to Table) DEPTH (Overall) SHIPPING WEIGHT

SHIPPING DIMENSIONS

Breaker or Fuse with a 40 AQMP Rating

19.75" Square (50.2cm Square) 20 1/2" x 21" (52cm x 53cm) 3/4" FPT 79.875" (202.9cm) 71.25" (180.9cm) 49" (124.5cm) (111.8cm) 34" (86.4cm) 446 lbs. (202.3 kg) 60" L x 36" W x 78" H (152.4 cm x 91.4 cm x 198.1 cm)

ADS has built a strong history based on Customer Service, Quality and Reliability.

A Commitment to Excellence is the driving force behind American Dish Service.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

(C) 4/05