



**HAWK BPB25DA Axial  
3320 CFM Air Mover**



## Dry Floors, Circulate and Exhaust Air

The Hawk BPB25A Axial moves air efficiently with less power and effort than other models. A built-in GFCI Auxiliary Outlet\* reduces risk of electric shock in wet areas. The BPB25A shoots a beam of air 50 feet ahead. An optional mounting stand locks onto the chassis and allows for 360 degree rotation to move air in any direction.

\*Required for use when Insurance Companies are paying for water and flood cleanup claims

### Engineered Design

- 2-Speed, 1/4 HP motor. A sealed motor design prevents moisture from entering and damaging internal motor components. 25 ft. 14 AWG foot power cord
- Axial design is efficient and produces up to 3320 CFM
- The metal air intake screen prevents objects from entering and damaging blades or motor
- Two 12 Amp GFCI grounded auxiliary power outlets on the side-mounted control panel. GFCI reduces the risk of electric shock in wet areas and is required by insurance companies paying for water flood cleanup claims.
- Use daisy chain in-line connection of up to 5 units for greater and more effective air flow
- 2-speed toggle switch with LED light on/off indicator
- Hour meter on control panel tracks hours of operation
- Strong roto-molded chassis has a profile that allows for vertical stacking of up to 5 units for convenient storage
- An optional folding metal frame with quick release locking knob allows easy adjustment for 360 degree airflow direction
- C-ETL US listed
- 2 year warranty on parts. 5 year warranty on the roto-molded chassis.

### Specifications

<b>Model</b>	BPB25DA Axial
<b>Motor / Power</b>	1/4 HP, 2-Speed, 115V, 60 Hz, Sealed Motor
<b>Motor CFM</b>	3320 CFM Max
<b>Amp Draw</b>	2.6 Amp (High Speed), 1.3 Amp (Low Speed)
<b>Power Cord with Molded Plug</b>	25 Ft. 14 AWG
<b>Air Flow</b>	360 degrees
<b>Meters</b>	Timer, LED PowerYes
<b>Size (H x W x L)</b>	20" x 13" x 22.5"
<b>Construction</b>	Sturdy Rotomolded Plastic
<b>Stackable</b>	5 units
<b>Daisy Chain</b>	Yes - Up to 5 Units
<b>Size (L x W x H)</b>	22.5" x 13" x 20"
<b>Weight</b>	30 lbs. (net) / 34 lbs. (gross)
<b>Sound Level</b>	78 dB
<b>Certification</b>	C-ETL-US

Subject to Change Without Notice



The Chassis is Rotomolded with a Profile for Stacking and Convenient Storage



Add the Folding Metal Frame to Direct Air at Every Angle



(2) GFCI Outlets and Convenient 2-Speed Switch



GFCI Shock-Preventing Outlets Make Daisy Chain Connection Easy